



CEWELD CuNi10ZnF

TYPE	CuZnNi high strength flux coated brazing alloy.				
ANWENDUNGEN	Joining: Steels, Galvanized steel, Tempered Cast Iron, Cast iron, Nickel alloys etc. This alloy is mainly used in the furniture and the bicycle industry for high strength joining of steels, also is this alloy recommended for rebuilding cock wheels due to the good sliding properties.				
EIGENSCHAFTEN	High strength brass alloy containing Nickel for more strength and bridging capability during brazing. Due to the special flux coating this type is mostly used in maintenance and repair, the flux coated rod can be bended very well without losing flux.				
KLASSIFIKATION	AWS EN ISO W.Nr. F-nr	A 5.8: RBCuZn-D 17672: Cu 773 2.0711 106			
GEEIGNET FÜR	Steels, Galvanized steel, Tempered Cast Iron, Cast iron, Nickel alloys				
ZULASSUNGEN					
SCHWEISSPOSITIONEN	      				
TYPISCHE CHEMISCHE ANALYSE DES FÜLLMETALLS (%)	Si 0.1	Ni 10	Cu 48		
MECHANISCHE GÜTEWERTE	Heat Treatment As Welded	R _{P0,2} (MPa)	R _m (MPa) 800	A5 (%) Hardness 180 HB	
RÜCKTROCKNUNG	Not required				
MELTING RANGE	890 - 920°C				
GAS ACC. EN ISO 14175	I1				