



CEWELD AA 2594M

TYPE	Metal cored wire designed for welding 25Cr type duplex stainless									
ANWENDUNGEN	Duplex stainless steels in chemical industry such as offshore, tubing, vessel, boilers etc									
EIGENSCHAFTEN	AA 2594M is a metal cored wire designed for welding 25Cr type duplex stainless steels especially for Super Duplex grade. Excellent productivity, improved weldability, better wetting properties compared to solid wires. Excellent weld metal quality and X-ray soundness									
KLASSIFIKATION	AWS	A 5.22: ~E2594T1-1								
	EN ISO	17633-A: T 25 9 4 Cu N L M M12 1								
	W.Nr.	1.4410								
	F-nr	6								
	FM	5								
GEEIGNET FÜR	1.4507, 1.4410, 1.4468, 1.4515, 1.4517, 1.4501, 1.4467, 1,4569, 1.4508 X2 CrNiMoCuN 25-6-3, X2 CrNiMoN 25-7-4, GX2 CrNiMoN 25-6-3, GX2 CrNiMoCuN 26-6-3, GX2 CrNiMoCuN 25-6-3-3, X2 CrNiMoCuWN 25-7-4, X2CrMnNiMoN26-5-4, X 2 CrNiMoN 26 7 4, GX2CrNiMoCuWN25-8-4 UNS S32520, S32550, S32750, S39274, S39277, S39553, S32760, J93380 Ferrallium 255, SAF 2507, ZERON 100, UR 76 N, SM22Cr, SAF 2507, Alloy 2507, Alloy 2594, Super Duplex									
ZULASSUNGEN	CE									
SCHWEISSPOSITIONEN	PAPBPCPF									
TYPISCHE CHEMISCHE ANALYSE DES SCHWEISSMETALLS (%)	C	Si	Mn	P	Cr	Ni	Mo	N	Cu	S
	0.025	0.6	1.4	0.025	25.5	9	3.5	0.25	0.6	0.015
MECHANISCHE GÜTEWERTE	Heat Treatment	R _{P0,2} (MPa)	R _m (MPa)	A ₅ (%)	Impact Energy (J) ISO-V				Hardness	
					-46°C					
	As Welded	580	680	20	40				HRc	
RÜCKTROCKNUNG	Not required									
GAS ACC. EN ISO 14175	M21									



CEWELD AA 2594M

AA 2594M 1,2MM

Packaging	KG/unit	EanCode
BS-300	15	8720663414786