CEWELD Ceramic Backing strip Ø shaped

certilas® THE FILLER METAL SPECIALIST

TYPE

Keramische backing strip Rond

TOEPASSINGEN

Keramische onderlegstrips, ook wel bekend als lassteentjes, optimaliseren lasverbindingen door hogere lassnelheden, verbeterde doorlassing en stabiliteit van het lasbad te bevorderen. Ze zijn universeel inzetbaar voor diverse lasprocessen en posities, waardoor ze een veelzijdige oplossing vormen voor verschillende lasbehoeften.

EIGENSCHAPPEN

Verkrijgbaar in de afmetingen:

Ø (mm)	Lengte (mm)
6	600
8	600
10	600
12	600
15	600

CLASSIFICATIE

GESCHIKT VOOR

one side welding with high currents in shipbuilding, pressure vessel fabrication, machine construction, crane building, tank, and general steel building.

GOEDKEURINGEN

LASPOSITIES

MECHANISCHE WAARDEN

HERDROGEN

Not required

GAS ACC. EN ISO 14175

CEWELD Ceramic Backing strip Ø shaped

CERAMIC BACKING STRIP Ø SHAPED Ø 10MM

Packaging	KG/unit	EanCode
0,6	60 meters per box	8720663410856

CERAMIC BACKING STRIP Ø SHAPED Ø 12MM

Packaging	KG/unit	EanCode
0,6	54 meters per box	8720663410863

CERAMIC BACKING STRIP Ø SHAPED Ø 15MM

Packaging	KG/unit	EanCode
0,6	42 meters per box	8720663410870

CERAMIC BACKING STRIP Ø SHAPED Ø 6MM

Packaging	KG/unit	EanCode
0,6	90 meters per box	8720663410832

CERAMIC BACKING STRIP Ø SHAPED Ø 8MM

Packaging	KG/unit	EanCode
0,6	72 meters per box	8720663410849