



CEWELD SACW 460 1W

TYPE	Highly basic flux cored wire for submerged arc welding					
TOEPASSINGEN	Especially for applications in shipbuilding and pipe production.					
EIGENSCHAPPEN	SACW460-1W is a cored wire with micro-alloy elements, which enables welding of one side with one layer and layer counter layer with very good quality values. Also available in the variants 2-3W in combination with solid wir					
CLASSIFICATIE	AWS EN ISO	A 5.23: F8A6-ECG 14171-A: S 46 4 FB T3				
GESCHIKT VOOR	S355ML-S460ML, S460Q, S460QL, P355GH, P355N-P460N, P355NL2-P460NL2, P355M-P460M, P355ML2-P460ML2, P355Q-P460Q Shipbuilding grades A-E, AH40-FH40					
GOEDKEURINGEN						
LASPOSITIES						
TYPICAL CHEMICAL ANALYSIS OF WELD METAL (%)	C	Si	Mn	P	S	
	0.03	0.6	1.8	0.02	0.02	
MECHANISCHE WAARDEN	Heat Treatment	R _{P0,2} (MPa)	R _m (MPa)	A ₅ (%)	Impact Energy (J) ISO-V	
					-20°C	-40°C
	As Welded	470	560	22	100	80
					Hardness	
					HRc	
HERDROGEN	Not required					
GAS ACC. EN ISO 14175						