



CEWELD DUR 12 Tig

TYPE Cobalt-based thermo shock resistant alloy for overlay applications.

TOEPASSINGEN Steam-valves, high temperature liquid pumps, hot cutting tools, cutting tools for plastic, wood and paper as well as high stressed sealings and sliding surfaces.

EIGENSCHAPPEN Outstanding alloy against abrasion, thermo-shock and corrosion combined with high temperatures. The weld deposit can be machined with tungsten tool tips and by grinding. The hardness of the weld deposit will degrees 20% at 600°C and has a nominal hardness of 49-53 HRc at room temperature. The weld deposit is high heat resistant up to 900°C. DUR 12 offers a low coefficient of friction of and exceptional resistance to galling. It has cavitation-erosion resistance ten times that of 304 stainless steel, DUR12 can be used to protect bearing surfaces in non-lubricating conditions due to its resistance to metal-to-metal wear.

CLASSIFICATIE AWS A 5.21: ERCoCr-B
EN ISO 14700: S Co3
F-nr 71

GESCHIKT VOOR Stellite 12 alloy for hardfacing steam-valves, high temperature liquid pumps, hot cutting tools, cutting, tools for plastic, wood and paper as well as high stressed sealings and, sliding surfaces.

GOEDKEURINGEN

LASPOSITIES



TYPICAL CHEMICAL ANALYSIS OF THE FILLER METAL (%)

| C | Si | Mn | Cr | Fe | W | Co |
|-----|-----|-----|----|-----|---|------|
| 1.4 | 0.8 | 0.1 | 29 | 2.5 | 8 | Rem. |

MECHANISCHE WAARDEN

| Heat Treatment | R _{P0.2} (MPa) | R _m (MPa) | A5 (%) | Hardness |
|----------------|-------------------------|----------------------|--------|----------|
| As Welded | | | | 48 HRc |

HERDROGEN Not required

GAS ACC. EN ISO 14175 I1



CEWELD DUR 12 Tig

| | | | |
|-------------------------|-----------|---------|---------------|
| DUR 12 TIG 2,4 X 1000MM | Packaging | KG/unit | EanCode |
| | Tube | 5 | 8720663402370 |
| DUR 12 TIG 3,2 X 1000MM | Packaging | KG/unit | EanCode |
| | Tube | 5 | 8720663402387 |
| DUR 12 TIG 4,0 X 1000MM | Packaging | KG/unit | EanCode |
| | Tube | 5 | 8720663402394 |
| DUR 12 TIG 5,0 X 1000MM | Packaging | KG/unit | EanCode |
| | Tube | 5 | 8720663402400 |
| DUR 12 TIG 6,4 X 1000MM | Packaging | KG/unit | EanCode |
| | Tube | 5 | 8720663402417 |